

DDP 60

Single Drum Puller



HOGG & DAVIS, Inc.

***Designers and
Manufacturers
of Line
Construction
Equipment***

RUGGED DEPENDABILITY

ODP 60

Single Drum Puller



Single-Drum Puller		
Performance:		
Line Pull Rating	Continuous	6,000lbs-Full Drum
Speed	Infinitely Variable	0.0-4.0 MPH-Full Drum
Drum Capacity:		
Rated Diameter	58"	
Width	44"	
Core Diameter	12"	
Rope Rated Capacity	15,000' of 3/4" Diameter	
Number of Drums	1	
Drive System:		
Engine	69.3 hp @ 3000 rpm 4TNV98C-DYEM Yanmar Diesel	
Hydraulic Drive	Closed Loop Hydrastatic	
Drive Train Brake	Spring Applied/ Hydraulically Released	
Drum Engagement	Manual mechanical clutch at drive motor	
Over-Spin Brake	16" Diameter Vented Bronze Rotor	
Brake Actuator	Accumulator with rotary adjustment	
Unit Dimensions:		
Length	209" (17'10")	
Width	100" (8'4")	
Height	103" (8'6")	
Weight (With Rope and Fluids)	11,000lbs	
Description:		
<p>The ODP60 single-drum puller is capable of line pull of 6,000lbs An Over-spin brake with a hydraulic actuator is on the drum. Operator controlled post style level wind allows for even winding of the rope. All unit functions are centrally located at the operator's station. Engine display includes tachometer, temp, and voltage. Pulling is controlled with an electric over hydraulic joystick allowing for infinite control of line speed.</p>		



Optional Equipment:
Hydraulic Tongue Jack (1)
Hydraulic Rear Outriggers (2)
Hydraulic Outriggers (3)
Tool Circuit: 10GPM, Soliniod Control
Spare Tire and Wheel
Under ground level wind

Product improvements may be introduced at any time, specifications are subject to change without notice.



**P.O.Box 405
 3800 Eagle Loop
 Odell, Oregon 97044
 TEL(541)354-1001
 FAX(541)354-1080**

**Visit us at
www.hoggdavis.com**