

DLT 388

Bull Wheel Tensioner



HOGG & DAVIS, Inc.

**Designers and
Manufacturers
of Line
Construction
Equipment**

RUGGED DEPENDABILITY

OLT38B

Bull Wheel Tensioner



Multi Grooved Bull Wheel Tensioner:

| | |
|----------------------------------|--|
| Rated: | 3,000 lbs |
| Bull Wheel Diameter with lining: | 38" |
| Liners: | |
| Number of Liners | 3 Pieces per Bullwheel |
| Groove Diameter | 1 1/2 " |
| Brake Specifications: | |
| Brakes | (2) 1 3/8" Stainless Steel Rotors w/Hydraulic Calipers |
| Diameter | 24" |
| Braking Mechanism | Hydraulic Control |
| Actuator | Single Screw w/ Pressure Gauge |
| Reel Capacity: | |
| Reel Capacity | 8,000 lbs |
| Maximum Reel Width | 56" |
| Maximum reel Diameter | 90" |
| Anti-Overspin Brake | 16" |
| Unit Dimensions: | |
| Length | 248" (20'8") |
| Width | 97" (8'1") |
| Height | 106" (8'10") |
| Weight | 4,000 lbs |

Description:

The OLT38B Bull Wheel Tensioner is designed to install right hand single lay conductor. The Bull Wheels are offset per IEEE Specifications to prevent unnecessary twisting of the conductor during installation. Bull Wheels are outfitted with replaceable molded segments. Molding of the segments in this manner eliminates the gaps of the segments and creates a smooth groove for the conductor to rest in. 24" disc brakes with centralized braking controls allow for precise tensioning of the conductor. The reel cargo area allows for a reel up to 90" in diameter and 56" wide and a maximum weight of 8,000lbs. A hydraulically actuated overspin brake is also included as well as a urethane fairlead for the conductor to glide through to the Bull Wheels.



Optional Equipment:

| |
|---|
| Hydraulic Tongue Jack |
| Hydraulic Outriggers (2) Rear |
| Hydraulic Reel Drive Retriever |
| Hydraulic Reel Drive Retriever (Tool Circuit) |
| Spare Tire and Wheel |
| 13HP Power Pack |

Product improvements may be introduced at any time, specifications are subject to change without notice.



**P.O.Box 405
3800 Eagle Loop
Odell, Oregon 97044
TEL(541)354-1001
FAX(541)354-1080**

**Visit us at
www.hoggdavis.com**