

DLT 728

Bull Wheel Tensioner



HOGG & DAVIS, Inc.

**Designers and
Manufacturers
of Line
Construction
Equipment**

RUGGED DEPENDABILITY

OLT72B

Bull Wheel Tensioner



Multi Grooved Bull Wheel Tensioner:

Rated:	10,000 lbs
Bull Wheel Diameter with lining:	72"
Liners:	
Number of Liners	8 Pieces per Bullwheel
Groove Diameter	2 1/2 "
Brake Specifications:	
Brakes	(4) 1 3/8" Stainless Steel Rotors w/Hydraulic Calipers
Diameter	48"
Braking Mechanism	Hydraulic Control
Actuator	Single Screw w/ Pressure Gauge
Unit Dimensions:	
Length	217" (18'1")
Width	96" (8')
Height	122" (10'2")
Weight	11,500 lbs

Description:

The OLT72B Bull Wheel Tensioner is designed to install right hand single lay conductor. The Bull Wheels are canted per IEEE Specifications to prevent unnecessary twisting of the conductor during installation. Bull Wheels are outfitted with replaceable molded segments. Molding of the segments in this manner eliminates the gaps of the segments and creates a smooth groove for the conductor to rest in. 48" disc brakes with centralized braking controls allow for precise tensioning of the conductor.



Optional Equipment:

Hydraulic Tongue Jack
Hydraulic Outriggers (2) Rear
Spare Tire and Wheel

Product improvements may be introduced at any time, specifications are subject to change without notice.



P.O.Box 405
3800 Eagle Loop
Odell, Oregon 97044
TEL(541)354-1001
FAX(541)354-1080

Visit us at
www.hoggdavis.com